

Sustainable concrete mix design for a target strength and service life

Julia G. Tapali^{1a}, Sotiris Demis^{2b} and Vagelis G. Papadakis^{*1}

¹*Department of Environmental and Natural Resources Management,
University of Patras, Agrinio, Greece*

²*Department of Civil Engineering, University of Patras, Patras, Greece*

(Received December 22, 2012, Revised June 19, 2013, Accepted August 15, 2013)

Abstract. Considering the well known environmental issues of cement manufacturing (direct and indirect levels of CO₂ emissions), clinker replacement by supplementary cementing materials (SCM) can be a very promising first step in reducing considerably the associated emissions. However, such a reduction is possible up to a particular level of SCM utilization, influenced by the rate of its pozzolanic reaction. In this study a (4-step) structured methodology is proposed in order to be able to further adjust the concrete mix design of a particular SCM, in achieving additional reduction of the associated levels of CO₂ emissions and being at the same time accepted from a derived concrete strength and service life point of view. On this note, the aim of this study is twofold. To evaluate the environmental contribution of each concrete component and to provide the best possible mix design configuration, balanced between the principles of sustainability (low environmental cost) and durability (accepted concrete strength and service life). It is shown that such a balance can be achieved, by utilising SCM by-products in the concrete mix, reducing in this way the fixed environmental emissions without compromising the long-term safety and durability of the structure.

Keywords: compressive strength; concrete; environmental cost; optimization; service life; supplementary cementing materials; sustainability

1. Introduction

Today, the cement and concrete industry is the dominant type of materials industry within the construction sector. Concrete is recognized to be the most widely used construction material, second only to water in total volumes consumed annually by society. It has been estimated that its average consumption is about 1 tonne per year per every person on the planet (Flower and Ganjayan 2007). Latest estimations from CEMBUREAU (2011) show a 0.7% rise in the EU construction activity in the first quarter of 2011, with the index of cement manufacturing showing a positive trend since the beginning of 2011. It is predicted that global demand for cement is expected to rise 4.1% yearly through 2013, to 3.5 billion metric tonnes in 2013. In general, at the

*Corresponding author, Professor, E-mail: vgp@psp.org.gr

^aPh.D. Candidate, E-mail: j.tapali@gmail.com

^bPh.D., E-mail: sdemis@upatras.gr

- performance concrete in marine structures”, *Const Build Mater.*, **21**, 878-884.
- IEA (2010), *International Energy Agency*, Energy Technology Systems Analysis Programme (ETSAP) – Technology Brief 103 – Cement Production, IEA Publications, Paris, France.
- IPPC (2010), Integrated Pollution Prevention and Control (IPPC) Bureau, Reference document of best available techniques in the cement, lime and magnesium oxide manufacturing industries, European Commission, Joint Research Centre, Institute for Prospective Technological Studies, Seville, Spain.
- Italcementi (2011), *Sustainability Disclosure*, Italcementi Group, Italy.
- Khunthingkeaw, J., Tangtermisirikul, S. and Leelawat, T. (2006), “A study on carbonation depth prediction for fly ash concrete”, *Const. Build. Mater.*, **20**, 744-753.
- Lafarge (2011), *Sustainability 11th Report*, Lafarge Group, France.
- Lo, T.Y., Nadeem, A., Tang, W.C.P. and Yu, P.C. (2009), “The effect of high temperature curing on the strength and carbonation of pozzolanic structural lightweight concretes”, *Const Build Mater.*, **23**, 1306-1310.
- Newlands, M.D., Jones, M.R., McCarthy, N.J. and Zheng, L. (2012), “Using fly ash to achieve low embodied CO₂ concrete”, *Proceedings of EUROCOALASH 2012 Conference*, Thessaloniki, Greece.
- Nochaiya, T., Wongkeo, W. and Chaipanich, A. (2010), “Utilization of fly ash with silica fume and properties of portland cement-fly ash-silica fume concrete”, *Fuel*, **89**, 768-774.
- Papadakis, V.G. (1999a), “Experimental investigation and theoretical modeling of silica fume activity in Concrete”, *Cement Concrete Res.*, **29**(1), 79-86.
- Papadakis, V.G. (1999b), “Effect of fly ash on portland cement systems. Part I: low calcium fly ash”, *Cement Concrete Res.*, **29**(11), 1727-1736.
- Papadakis, V.G. (2000), “Effect of supplementary cementing materials on concrete resistance against carbonation and chloride ingress”, *Cement Concrete Res.*, **30**, 291-299.
- Papadakis, V.G., Vayenas, C.G. and Fardis, M.N. (1991), “Fundamental modeling and experimental investigation of concrete carbonation”, *ACI Mater. J.*, **88**, 363-373.
- Papadakis, V.G. and Tsimas, S. (2002), “Supplementary cementing materials in concrete Part I: Efficiency and design”, *Cement Concrete Res.*, **32**, 1525-1532.
- Papadakis, V.G., Antiohos, S. and Tsimas, S. (2002), “Supplementary cementing materials in concrete - part II: A fundamental estimation of the efficiency factor”, *Cement Concrete Res.*, **32**(10), 1533-1538.
- Papadakis, V.G., Efstathiou, M.P. and Apostolopoulos, C.A. (2007), “Computer-aided approach of parameters influencing concrete service life and field validation”, *Comput. Concr.*, **4**, 1-18.
- Papadakis, V.G. and Demis, S. (2013), “Predictive modeling of concrete compressive strength based on cement strength class”, *Comput. Concr.*, **11**(6), 587-602.
- Ruffolo, J., Lee, P. and Stewart, D. (2010), *Technology predictions*, Deloitte Touche Tohmatsu. London.
- Sweeny, B. and Sceats, M. (2009), “Calix – A carbon capture breakthrough”, *Carbon Capture J.*, **12**, 19-21.
- U.S. Environmental Protection Agency (2008), *Guidebook for Using the Tool BEST Cement: Benchmarking and Energy Savings Tool for the Cement Industry*, Lawrence Berkeley National Laboratory, Berkeley, USA.
- Valcuende, M. and Parra, C. (2010), “Natural carbonation of self-compacting concretes”, *Const. Build. Mater.*, **24**, 848-853.
- WBCSD (2005), World Business Council for Sustainable Development, Cement sustainability Initiative. Guidelines for the selection and use of fuels and raw materials in the cement manufacturing process, Geneva, Switzerland.
- WBSCD (2009), World business council for sustainable development, Cement Technology Roadmap 2009 – Carbon emissions reductions up to 2050, Geneva, Switzerland.
- Zampini, D. (2009), Future developments of concrete in the construction materials industry, Chapter 21, Vol. 1, Thomas Telford.